

**MODEL:** PJ-103H-MSMT-TR | **DESCRIPTION:** DC POWER JACK**FEATURES**


- 3 conductor with signal pin
- reflow solder
- tape & reel packaging

**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			42		Vdc
rated input current	power pin			10	A
	signal pin			3	A
contact resistance				50	mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-20		70	°C
storage temperature		-40		85	°C
life			5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	5~35°C, <75% humidity				°C
reflow soldering	see reflow profile			260	°C
drying conditions	bake at 120°C for 4 hours				



MECHANICAL DRAWING

units: mm

tolerance:

X. ± 0.50 mm

X.X ±0.25 mm


X.XX ±0.15 mm

X.XXX ±0.10 mm


PCB: ± 0.05 mm

unless otherwise specified


PCB thickness: 1.4 mm



ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	housing	PA10T (UL94V-0)	black
2	terminal 1 & 2	copper alloy t=0.30	contact area: 3 μ " gold solder area: tin over nickel
3	terminal 3 & 4	copper alloy t=0.25	contact area: 3 μ " gold solder area: tin over nickel
4	terminal 5	copper alloy t=0.30	contact area: 3 μ " gold solder area: tin over nickel
5	shield	SUS 304 t=0.30	nickel



Recommended PCB Layout
Top View



MATING PLUG
Jack Insertion Depth: 9.0 mm


Schematic	
Model	PJ-103H-MSMT-TR
terminals 1 & 2	V+
terminals 3 & 4	V-
terminal 5	signal pin

PACKAGING

units: mm

Reel Size: $\varnothing 330$ mm

Reel QTY: 300 pcs per reel



REVISION HISTORY

rev.	description	date
1.0	initial release	09/23/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com